

Matting Agent

Technical Data Sheet #4100



Components

4100 Matting Agent

Mix by Volume

- Product is designed to be mixed with Lumabase 1000 and 2000 Clear Coats as recommended below.
- Product can be mixed by weight at different levels to achieve the below desired levels of gloss.
 - Flat = 0–15 gloss level
 - Satin = 20–45 gloss level
 - Semi = 50–65 gloss level

Application

- 4100 **must** be shaken thoroughly before each use.

Refer to all labels on products and information sheets for hazards and proper handling procedures for each component. Read the Safety Data Sheets (SDS) supplied with the materials.

KEEP OUT OF REACH OF CHILDREN

	<i>PINT GRAMS</i>		<i>PINT GRAMS</i>
FLAT			
2000 4:1 Clear	249.1	1000 4:1 Economy Clear	247.8
2002 Med Activator	62.1	1002 Med Activator	64.6
4100 Matting Agent	179.6	4100 Matting Agent	169.7
SATIN			
2000 4:1 Clear	264.5	1000 4:1 Economy Clear	266.0
2002 Med Activator	65.9	1002 Med Activator	69.4
4100 Matting Agent	155.8	4100 Matting Agent	139.8
SEMI			
2000 4:1 Clear	282.1	1000 4:1 Economy Clear	285.4
2002 Med Activator	70.3	1002 Med Activator	74.4
4100 Matting Agent	126.0	4100 Matting Agent	108.6

Disposal

Dispose of all paint and paint related materials in accordance with state and local regulations.

Safety & Health

Read and follow all technical product information, labels, and SDS prior to application. Keep product out of reach of children and animals. Always wear proper safety equipment (respirator, gloves, eye, and clothing protection) when using this product.