

SAFETY DATA SHEET

1003

Version: 1.0

US - en

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

| | | |
|--------------------------|---|--------------------------|
| Product name | ECONO-CLEAR SLOW ACTIVATOR | |
| Product code | 1003 | |
| Formula date | 2019-01-25 | |
| Recommended use | Hardener for professional use | |
| Responsible party | Pro Line Performance Products PO Box 1136 Olympia, WA 98507 | |
| Telephone | Product information | www.LumabaseCoatings.com |
| | Medical emergency | 800-535-5053 |
| | Transportation emergency | 800-535-5053 |

2. HAZARDS IDENTIFICATION

GHS-Classification

Flammable liquids, Category 3 ; Skin corrosion/irritation, Category 2 ; Serious eye damage/eye irritation, Category 2A ; Skin sensitisation, Category 1 ; Carcinogenicity, Category 2 ; Target Organ Systemic Toxicant - Single exposure, Category 3

GHS-Labeling

Hazard symbols:



Signal word: Warning

Hazard statements: Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements: Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ vapours/ spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplemental first aid instructions on this label). If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local regulations.

Other hazards which do not result in classification

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

SAFETY DATA SHEET

1003

Version: 1.0

US - en

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

0 %

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of synthetic resins and solvents

Components

| CAS-No. | Chemical name | Concentration |
|------------|--------------------------------|---------------|
| 103-09-3 | 2-ethylhexyl acetate | 4 - 15% |
| 108-67-8 | 1,3,5-trimethyl benzene | 1 - 4% |
| 123-86-4 | Butyl acetate | 1 - 4% |
| 28182-81-2 | Aliphatic polyisocyanate resin | 37 - 48% |
| 64742-94-5 | Aromatic hydrocarbon | 15 - 26% |
| 64742-95-6 | Aromatic hydrocarbon | 4 - 15% |
| 91-20-3 | Naphthalene | 1.3% |
| 95-63-6 | 1,2,4-trimethyl benzene | 8% |
| 98-82-8 | Cumene | 0.8% |

Any concentration shown as a range is due to batch variation.

Non-regulated ingredients 1 - 5%

OSHA Hazardous: Yes

4. FIRST AID MEASURES

Eye contact: Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact: Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation: Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion: If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed

Inhalation: May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may

SAFETY DATA SHEET

1003

Version: 1.0

US - en

be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion: May result in gastrointestinal distress.

Skin or eye contact: May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. Skin contact may cause skin sensitization.

Indication of Immediate medical attention and special treatment needed if necessary: No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical

Extinguishing media which shall not be used for safety reasons: High volume water jet

Hazardous combustion products: CO, CO₂, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

Fire and Explosion Hazards: Combustible liquid. When heated above the flashpoint, emits vapors which, when mixed with air, will burn if an ignition source is present. Fine mist or sprays could ignite at temperatures below the flashpoint.

Special Protective Equipment and Fire Fighting Procedures: Full protective flameproof clothing should be worn as appropriate. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

6. ACCIDENTAL RELEASE MEASURES

Procedures for cleaning up spills or leaks: Ventilate area. If heated above the flashpoint, remove sources of ignition. Do not breathe vapors. Do not get in eyes or on skin. Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C), eye protection, gloves and protective clothing. Pour liquid decontamination solution over the spill and allow to sit at least 10 minutes. Typical decontamination solutions for isocyanate containing materials are: 20% Surfactant (Tergitol TM 10) and 80% Water OR 0-10% Ammonia, 2-5% Detergent and Water (balance) Confine and remove with inert absorbent. Pressure can be generated. Do not seal waste containers for 48 hours to allow CO₂ to vent. After 48 hours, material may be sealed and disposed of properly.

Environmental precautions: Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

7. HANDLING AND STORAGE

Precautions for safe handling: Observe label precautions. Keep away from heat, flame and other sources of ignition. When heated above its flash point, this must be handled as if it were a flammable liquid. Close container after each use. Do not transfer contents to bottles or unlabeled containers. Wash thoroughly after handling and before eating or smoking. If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

SAFETY DATA SHEET

1003

Version: 1.0

US - en

Advice on protection against fire and explosion: Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

Storage

Requirements for storage areas and containers: Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage: Store separately from oxidizing agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Precautions should be taken to avoid exposure to atmospheric humidity or water. Evolution of CO₂ in closed containers causes overpressure and produces a risk of bursting.

Additional information on storage conditions: Precautions should be taken to avoid exposure to atmospheric humidity or water. Humid air and/or water will produce carbon dioxide which will pressurize the container. Open drum carefully as content may be under pressure.

OSHA/NFPA Storage Classification: II

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls and work practices: Provide adequate ventilation.

National occupational exposure limits

| CAS-No. | Chemical name | Source | Time | Type | Value | Note |
|----------|-------------------------|--------|--------|------|---------|------|
| 95-63-6 | 1,2,4-trimethyl benzene | ACGIH | 8 hr | TWA | 25 ppm | |
| | | OSHA | 8 hr | TWA | 25 ppm | |
| 108-67-8 | 1,3,5-trimethyl benzene | ACGIH | 8 hr | TWA | 25 ppm | |
| 123-86-4 | Butyl acetate | ACGIH | 15 min | STEL | 200 ppm | |
| | | ACGIH | 8 hr | TWA | 150 ppm | |
| | | OSHA | 8 hr | TWA | 150 ppm | |
| 91-20-3 | Naphthalene | ACGIH | | CEIL | 15 ppm | Skin |
| | | ACGIH | 8 hr | TWA | 10 ppm | Skin |
| | | OSHA | 8 hr | TWA | 10 ppm | |
| 98-82-8 | Cumene | ACGIH | 8 hr | TWA | 50 ppm | |
| | | OSHA | 8 hr | TWA | 50 ppm | Skin |

Glossary

| | |
|------|---------------------------|
| CEIL | Ceiling exposure limit |
| STEL | Short term exposure limit |
| TL | Threshold limits |
| TLV | Threshold Limit Value |
| TWA | Time weighted average |
| TWAE | Time-Weighted Average |

Protective equipment: Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection: Do not breathe vapors or mists. Wear a positive-pressure, supplied air respirator (NIOSH approved TC-19C), while mixing activator with paint, during application and until all vapors and spray mists are exhausted. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Refer to the hardener/activator label instructions for further information. Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed to vapor or spray mist.

Eye protection: Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

SAFETY DATA SHEET

1003

Version: 1.0

US - en

Skin and body protection: Neoprene gloves and coveralls are recommended.

Hygiene measures: Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Environmental exposure controls: Do not let product enter drains.

For ecological information, refer to Ecological Information Section 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form: liquid **Colour:** clear

| | | |
|--|-------------------|---------------|
| Flash point | 119 °F | |
| Lower Explosive Limit | 0.6 % | |
| Upper Explosive Limit | 8.1 % | |
| Evaporation rate | Slower than Ether | |
| Vapor pressure of principal solvent | 2.0 hPa | |
| Water solubility | partly miscible | |
| Vapor density of principal solvent (Air = 1) | 4.1 | |
| Approx. Boiling Range | 146 °C | |
| Approx. Freezing Range | -93 – -20 °C | |
| Gallon Weight (lbs/gal) | 8.17 | |
| Specific Gravity | 0.98 | |
| Percent Volatile By Volume | 63.59% | |
| Percent Volatile By Weight | 57.05% | |
| Percent Solids By Volume | 36.41% | |
| Percent Solids By Weight | 42.95% | |
| pH (waterborne systems only) | Not applicable | |
| Partition coefficient: n-octanol/water | No data available | |
| Ignition temperature | 268 °C | DIN 51794 |
| Decomposition temperature | Not applicable. | |
| Viscosity (23 °C) | Not applicable. | ISO 2431-1993 |
| VOC* less exempt (lbs/gal) | 4.7 | |
| VOC* as packaged (lbs/gal) | 4.7 | |

* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

10. STABILITY AND REACTIVITY

Stability: Stable

Conditions to avoid: Stable under recommended storage and handling conditions (see section 7).

Materials to avoid: Keep away from oxidizing agents and strongly acid or alkaline materials. Amines and alcohols cause exothermic reactions. Mixture reacts slowly with water resulting in evolution of CO₂. Evolution of CO₂ in closed containers causes overpressure and produces a risk of bursting.

Hazardous decomposition products: When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen as well as hydrogen cyanide, amines, alcohols and water.

SAFETY DATA SHEET

1003

Version: 1.0

US - en

Hazardous Polymerization: Will not occur.

Sensitivity to Static Discharge: If heated above the flash point, solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

Sensitivity to Mechanical Impact: None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion: May result in gastrointestinal distress.

Skin or eye contact: May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity

not hazardous

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

not hazardous

% of unknown composition: 0 %

Skin corrosion/irritation

| | |
|-------------------------|------------|
| Aromatic hydrocarbon | Category 3 |
| 1,2,4-trimethyl benzene | Category 2 |
| 2-ethylhexyl acetate | Category 2 |
| Aromatic hydrocarbon | Category 3 |
| 1,3,5-trimethyl benzene | Category 2 |
| Butyl acetate | Category 3 |
| Cumene | Category 2 |

Serious eye damage/eye irritation

| | |
|-------------------------|-------------|
| 1,2,4-trimethyl benzene | Category 2A |
| 2-ethylhexyl acetate | Category 2B |
| 1,3,5-trimethyl benzene | Category 2A |
| Cumene | Category 2B |

Respiratory sensitisation

Not classified according to GHS criteria

SAFETY DATA SHEET

1003

Version: 1.0

US - en

Skin sensitisation

Aliphatic polyisocyanate resin Category 1

Germ cell mutagenicity

Not classified according to GHS criteria

Carcinogenicity

Naphthalene Category 2

Cumene Category 2

Toxicity for reproduction

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure

- **Inhalation**

Respiratory system Aliphatic polyisocyanate resin

Target Organ Systemic Toxicant - Repeated exposure

Not classified according to GHS criteria

Aspiration toxicity

Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.): No information available.

Symptoms related to the physical, chemical and toxicological characteristics:

Based on the properties of the isocyanate components and considering toxicological data on similar products, the following applies: This formulation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Components of the product may be absorbed into the body through the skin.

Whether the hazardous chemical is listed by NTP, IARC or OSHA:

Naphthalene IARC 2B

Naphthalene NTP Anticipated

Cumene IARC 2B

12. ECOLOGICAL INFORMATION

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

SAFETY DATA SHEET

1003

Version: 1.0

US - en

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

14. TRANSPORT INFORMATION

International transport regulations

IMDG (Sea transport)

UN number: 1263
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: III
Marine Pollutant: yes [Solvent naphtha (petroleum), heavy arom.]
EmS: F-E,S-E

ICAO/IATA (Air transport)

UN number: 1263
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: III

DOT

UN number: 1263
Proper shipping name: PAINT RELATED MATERIAL

Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: III
Marine Pollutant: yes [Solvent naphtha (petroleum), heavy arom.]

The transport information is for bulk shipments. Exceptions may apply for smaller containers.

Matters needing attention for transportation: Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. REGULATORY INFORMATION

TSCA Status: In compliance with TSCA Inventory requirements for commercial purposes.

DSL Status: All components of the mixture are listed on the DSL.

Photochemical Reactivity: Photochemically reactive

SAFETY DATA SHEET

1003

Version: 1.0

US - en

Regulatory information:

| CAS # | Ingredient | EPCRA | | | | CERCLA | CAA | |
|------------|--------------------------------|-------|-----|----|---------|--------|---------|---|
| | | 302 | TPQ | RQ | 311/312 | 313 | RQ(lbs) | |
| 28182-81-2 | Aliphatic polyisocyanate resin | N | NR | NR | A,C,R | N | NR | N |
| 64742-94-5 | Aromatic hydrocarbon | N | NR | NR | A | N | NR | N |
| 95-63-6 | 1,2,4-trimethyl benzene | N | NR | NR | A,C | Y | NR | N |
| 103-09-3 | 2-ethylhexyl acetate | N | NR | NR | A,F | N | NR | N |
| 64742-95-6 | Aromatic hydrocarbon | N | NR | NR | A,C,F | N | NR | N |
| 108-67-8 | 1,3,5-trimethyl benzene | N | NR | NR | NA | N | NA | N |
| 123-86-4 | Butyl acetate | N | NR | NR | A,C,F | N | NR | N |
| 91-20-3 | Naphthalene | N | NR | NR | A,C,F | Y | 100 | Y |
| 98-82-8 | Cumene | N | NR | NR | A,C,F | Y | NR | Y |

16. OTHER INFORMATION

HMIS rating: H: 2 ; F: 2 ; R: 1

Glossary of Terms

| | |
|-------|--|
| ACGIH | American Conference of Governmental Industrial Hygienists. |
| IARC | International Agency for Research on Cancer. |
| NTP | National Toxicology Program. |
| OEL | Occupational Exposure Limit |
| OSHA | Occupational Safety and Health Administration. |
| STEL | Short term exposure limit |
| TWA | Time-weighted average. |
| PNOR | Particles not otherwise regulated. |
| PNOC | Particles not otherwise classified. |

| | |
|--------------------|---|
| EPCRA | Emergency Planning and Community Right-to-know Act (aka Title III, SARA) |
| 302 | Extremely hazardous substances |
| 311/312 Categories | F = Fire Hazard A = Acute Hazard R = Reactivity Hazard C = Chronic Hazard P = Pressure Related Hazard |
| 313 Information | Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372. |
| CERCLA | Comprehensive Emergency Response, Compensation and Liability Act of 1980. |
| HAP | Listed as a Clean Air Act Hazardous Air Pollutant. |
| TPQ | Threshold Planning Quantity. |
| RQ | Reportable Quantity |
| NA | not available |
| NR | not regulated |

NOTE: The list (above) of glossary terms may be modified.

SAFETY DATA SHEET

1003

Version: 1.0

US - en

Information is accurate and subject to change as new information is received.

The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS Prepared by Regulatory Affairs

Report version

Version: 1.0

Changes:

Revision Date: 2019-03-05