

# SAFETY DATA SHEET

100

Version: 1.0

US - en

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

<b>Product name</b>	ETCH PRIMER (GREEN)	
<b>Product code</b>	100	
<b>Formula date</b>	2019-01-23	
<b>Recommended use</b>	Coating for professional use	
<b>Responsible party</b>	Pro Line Performance Products PO Box 1136 Olympia, WA 98507	
<b>Telephone</b>	Product information	www.LumabaseCoatings.com
	Medical emergency	800-535-5053
	Transportation emergency	800-535-5053

## 2. HAZARDS IDENTIFICATION

### GHS-Classification

Flammable liquids, Category 2 ; Skin corrosion/irritation, Category 2 ; Serious eye damage/eye irritation, Category 2A ; Skin sensitisation, Category 1 ; Carcinogenicity, Category 1A ; Toxicity for reproduction, Category 1B ; Target Organ Systemic Toxicant - Single exposure, Category 3 ; Target Organ Systemic Toxicant - Repeated exposure, Category 2

### GHS-Labeling

Hazard symbols:



Signal word: Danger

**Hazard statements:** Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements:** Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplemental first aid instructions on this label). If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local regulations.

### Other hazards which do not result in classification

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

# SAFETY DATA SHEET

100

Version: 1.0

US - en

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:  
9.2 %

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of synthetic resins, pigments, and solvents

### Components

CAS-No.	Chemical name	Concentration
100-41-4	Ethylbenzene	0.6%
108-88-3	Toluene	14%
110-43-0	Methyl amyl ketone	4 - 15%
117-81-7	Bis(2-ethylhexyl) phthalate	1.0%
1330-20-7	Xylene	2%
1333-86-4	Carbon black	0.3%
13463-67-7	Titanium dioxide	2.9%
14808-60-7	Quartz-crystalline silica	0.1%
540-88-5	T-butyl acetate	15 - 26%
67-64-1	Acetone	4 - 15%
67924-34-9	Bisphenol a epoxy resin	1 - 4%
75-65-0	Tertiary butyl alcohol	0.1%

Any concentration shown as a range is due to batch variation.  
Non-regulated ingredients 30 - 40%  
OSHA Hazardous: Yes

## 4. FIRST AID MEASURES

**Eye contact:** Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

**Skin contact:** Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

**Inhalation:** Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

**Ingestion:** If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

### Most Important Symptoms/effects, acute and delayed

# SAFETY DATA SHEET

100

Version: 1.0

US - en

**Inhalation:** May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**Ingestion:** May result in gastrointestinal distress.

**Skin or eye contact:** May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

**Indication of immediate medical attention and special treatment needed if necessary:** No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

## 5. FIREFIGHTING MEASURES

**Suitable extinguishing media:** Universal aqueous film-forming foam, Carbon dioxide (CO<sub>2</sub>), Dry chemical

**Extinguishing media which shall not be used for safety reasons:** High volume water jet

**Hazardous combustion products:** CO, CO<sub>2</sub>, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

**Fire and Explosion Hazards:** Flammable liquid. Vapor/air mixture will burn when an ignition source is present.

**Special Protective Equipment and Fire Fighting Procedures:** Full protective flameproof clothing should be worn as appropriate. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

## 6. ACCIDENTAL RELEASE MEASURES

**Procedures for cleaning up spills or leaks:** Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

**Environmental precautions:** Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Observe label precautions. Keep away from heat, sparks, flame, static discharge and other sources of ignition. VAPORS MAY CAUSE FLASH FIRE. Close container after each use. Ground containers when pouring. Do not transfer contents to bottles or unlabeled containers. Wash thoroughly after handling and before eating or smoking. Do not store above 49 °C (120 °F). If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

**Advice on protection against fire and explosion:** Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

# SAFETY DATA SHEET

100

Version: 1.0

US - en

## Storage

**Requirements for storage areas and containers:** Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**Advice on common storage:** Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

OSHA/NFPA Storage Classification: IB

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering controls and work practices:** Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### National occupational exposure limits

CAS-No.	Chemical name	Source	Time	Type	Value	Note
540-88-5	T-butyl acetate	ACGIH	8 hr	TWA	200 ppm	
		OSHA	8 hr	TWA	200 ppm	
108-88-3	Toluene	OSHA		CEIL	300 ppm	
		OSHA	10 min	TWA	500 ppm	
		OSHA	8 hr	TWA	200 ppm	
67-64-1	Acetone	ACGIH	15 min	STEL	750 ppm	
		ACGIH	8 hr	TWA	500 ppm	
		OSHA	8 hr	TWA	1,000 ppm	
110-43-0	Methyl amyl ketone	ACGIH	8 hr	TWA	50 ppm	
		OSHA	8 hr	TWA	100 ppm	
13463-67-7	Titanium dioxide	OSHA	8 hr	TWA	15 mg/m <sup>3</sup>	Total Dust
1330-20-7	Xylene	ACGIH	15 min	STEL	150 ppm	
		ACGIH	8 hr	TWA	100 ppm	
		OSHA	8 hr	TWA	100 ppm	
117-81-7	Bis(2-ethylhexyl) phthalate	ACGIH	8 hr	TWA	5 mg/m <sup>3</sup>	
100-41-4	Ethylbenzene	ACGIH	8 hr	TWA	20 ppm	
		OSHA	8 hr	TWA	100 ppm	
1333-86-4	Carbon black	ACGIH	8 hr	TWA	3 mg/m <sup>3</sup>	
		OSHA	8 hr	TWA	3.5 mg/m <sup>3</sup>	
75-65-0	Tertiary butyl alcohol	ACGIH	8 hr	TWA	100 ppm	
		OSHA	8 hr	TWA	100 ppm	
14808-60-7	Quartz-crystalline silica	OSHA	8 hr	TWA	0.3 mg/m <sup>3</sup>	Total Dust
		OSHA	8 hr	TWA	50 ug/m <sup>3</sup>	Respirable Dust

### Glossary

CEIL	Ceiling exposure limit
STEL	Short term exposure limit
TL	Threshold limits
TLV	Threshold Limit Value
TWA	Time weighted average
TWAE	Time-Weighted Average

**Protective equipment:** Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

**Respiratory protection:** Do not breathe vapors or mists. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A) during application and until all vapors

# SAFETY DATA SHEET

100

Version: 1.0

US - en

and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air-purifying respirator fit is not possible, wear a positive pressure, supplied-air respirator (NIOSH TC-19C). In all cases, follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area.

**Eye protection:** Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

**Skin and body protection:** Neoprene gloves and coveralls are recommended.

**Hygiene measures:** Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Environmental exposure controls:** Do not let product enter drains.

For ecological information, refer to Ecological Information Section 12.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

**Form:** liquid      **Colour:** green

Flash point	40 °F	
Lower Explosive Limit	1.1 %	
Upper Explosive Limit	12.8 %	
Evaporation rate	Slower than Ether	
Vapor pressure of principal solvent	27.6 hPa	
Water solubility	moderate	
Vapor density of principal solvent (Air = 1)	0	
Approx. Boiling Range	56 °C	
Approx. Freezing Range	-95 – 1300 °C	
Gallon Weight (lbs/gal)	8.85	
Specific Gravity	1.06	
Percent Volatile By Volume	75.08%	
Percent Volatile By Weight	60.66%	
Percent Solids By Volume	24.92%	
Percent Solids By Weight	39.35%	
pH (waterborne systems only)	Not applicable	
Partition coefficient: n-octanol/water	No data available	
Ignition temperature	393 °C	DIN 51794
Decomposition temperature	Not applicable.	
Viscosity (23 °C)	Not applicable.	ISO 2431-1993
VOC* less exempt (lbs/gal)	5.3	
VOC* as packaged (lbs/gal)	4.9	
VOC LE (TBAC)	4.2	
VOC AP (TBAC)	2.7	

\* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

TBAC is not universally recognized as an exempt solvent.

Users should consult the applicable regulations for their region.

# SAFETY DATA SHEET

100

Version: 1.0

US - en

## 10. STABILITY AND REACTIVITY

**Stability:** Stable

**Conditions to avoid:** Stable under recommended storage and handling conditions (see section 7).

**Materials to avoid:** None reasonably foreseeable.

**Hazardous decomposition products:** When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

**Hazardous Polymerization:** Will not occur.

**Sensitivity to Static Discharge:** Solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

**Sensitivity to Mechanical Impact:** None known.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Inhalation:** May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**Ingestion:** May result in gastrointestinal distress.

**Skin or eye contact:** May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

### Delayed and immediate effects and also chronic effects from short and long term exposure:

#### Acute oral toxicity

not hazardous

#### Acute dermal toxicity

not hazardous

#### Acute inhalation toxicity

not hazardous

% of unknown composition: 9.2 %

### Skin corrosion/irritation

T-butyl acetate	Category 3
Toluene	Category 2
Acetone	Category 3
Xylene	Category 2
Bisphenol a epoxy resin	Category 2
Ethylbenzene	Category 2

### Serious eye damage/eye irritation

T-butyl acetate	Category 2A
Acetone	Category 2A
Xylene	Category 2A

# SAFETY DATA SHEET

100

Version: 1.0

US - en

Bisphenol a epoxy resin Category 2A  
Tertiary butyl alcohol Category 2A

## Respiratory sensitisation

Not classified according to GHS criteria

## Skin sensitisation

Bisphenol a epoxy resin Category 1

## Germ cell mutagenicity

Not classified according to GHS criteria

## Carcinogenicity

Titanium dioxide Category 2  
Ethylbenzene Category 2  
Carbon black Category 2  
Quartz-crystalline silica Category 1A

## Toxicity for reproduction

Toluene Category 2  
Bis(2-ethylhexyl) phthalate Category 1B  
Tertiary butyl alcohol Category 2

## Target Organ Systemic Toxicant - Single exposure

- **Inhalation**

**Narcotic effects** Methyl amyl ketone

## Target Organ Systemic Toxicant - Repeated exposure

- **Inhalation**

**Respiratory system** Quartz-crystalline silica

## Aspiration toxicity

Not classified according to GHS criteria

**Numerical measures of toxicity (acute toxicity estimation (ATE),etc. ):** No information available.

## Symptoms related to the physical, chemical and toxicological characteristics:

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

## Whether the hazardous chemical is listed by NTP, IARC or OSHA:

Titanium dioxide IARC 2B  
Bis(2-ethylhexyl) phthalate IARC 2B  
Bis(2-ethylhexyl) phthalate NTP Anticipated  
Ethylbenzene IARC 2B  
Carbon black IARC 2B  
Quartz-crystalline silica IARC 1

# SAFETY DATA SHEET

100

Version: 1.0

US - en

## 12. ECOLOGICAL INFORMATION

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

## 14. TRANSPORT INFORMATION

### International transport regulations

#### IMDG (Sea transport)

UN number: 1263  
Proper shipping name: PAINT

Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: II  
Marine Pollutant: no  
EmS: F-E,S-E

#### ICAO/IATA (Air transport)

UN number: 1263  
Proper shipping name: PAINT

Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: II

#### DOT

UN number: 1263  
Proper shipping name: PAINT

Hazard Class: 3  
Subsidiary Hazard Class: Not applicable.  
Packing group: II  
Marine Pollutant: no

The transport information is for bulk shipments. Exceptions may apply for smaller containers.

**Matters needing attention for transportation:** Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.



# SAFETY DATA SHEET

100

Version: 1.0

US - en

## 15. REGULATORY INFORMATION

**TSCA Status:** In compliance with TSCA Inventory requirements for commercial purposes.

**DSL Status:** All components of the mixture are listed on the DSL.

**Photochemical Reactivity:** Photochemically reactive

**Regulatory information:**

CAS #	Ingredient	EPCRA					CERCLA RQ(lbs)	CAA HAP
		302	TPQ	RQ	311/312	313		
540-88-5	T-butyl acetate	N	NR	NR	A,C,F	N	NR	N
108-88-3	Toluene	N	NR	NR	A,C,F	Y	1,000	Y
67-64-1	Acetone	N	NR	NR	A,C,F	N	5,000	N
110-43-0	Methyl amyl ketone	N	NR	NR	A,C,F	N	NR	N
13463-67-7	Titanium dioxide	N	NR	NR	A	N	NR	N
1330-20-7	Xylene	N	NR	NR	A,C,F	Y	100	Y
67924-34-9	Bisphenol a epoxy resin	N	NR	NR	NA	N	NR	N
117-81-7	Bis(2-ethylhexyl) phthalate	N	NR	NR	C	Y	100	Y
100-41-4	Ethylbenzene	N	NR	NR	A,C,F	Y	1,000	Y
1333-86-4	Carbon black	N	NR	NR	C	N	NR	N
75-65-0	Tertiary butyl alcohol	N	NR	NR	C	Y	100	N
14808-60-7	Quartz-crystalline silica	N	NR	NR	A,C	N	NR	N

## 16. OTHER INFORMATION

**HMIS rating:** H: 2 ; F: 3 ; R: 0

**Glossary of Terms**

ACGIH	American Conference of Governmental Industrial Hygienists.				
IARC	International Agency for Research on Cancer.				
NTP	National Toxicology Program.				
OEL	Occupational Exposure Limit				
OSHA	Occupational Safety and Health Administration.				
STEL	Short term exposure limit				
TWA	Time-weighted average.				
PNOR	Particles not otherwise regulated.				
PNOG	Particles not otherwise classified.				
EPCRA	Emergency Planning and Community Right-to-know Act (aka Title III, SARA)				
302	Extremely hazardous substances				
311/312 Categories	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">F = Fire Hazard</td> <td>A = Acute Hazard</td> </tr> <tr> <td>R = Reactivity Hazard</td> <td>C = Chronic Hazard</td> </tr> </table>	F = Fire Hazard	A = Acute Hazard	R = Reactivity Hazard	C = Chronic Hazard
F = Fire Hazard	A = Acute Hazard				
R = Reactivity Hazard	C = Chronic Hazard				

# SAFETY DATA SHEET

100

Version: 1.0

US - en

	P = Pressure Related Hazard
313 Information	Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372.
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980.
HAP	Listed as a Clean Air Act Hazardous Air Pollutant.
TPQ	Threshold Planning Quantity.
RQ	Reportable Quantity
NA	not available
NR	not regulated

NOTE: The list (above) of glossary terms may be modified.

Information is accurate and subject to change as new information is received.

The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS Prepared by Regulatory Affairs

## Report version

**Version:** 1.0

**Changes:**

**Revision Date:** 2019-03-05