

SAFETY DATA SHEET

40

Version: 1.0

US - en

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name	DTM LT GRAY EPOXY PRIMER	
Product code	40	
Formula date	2019-01-22	
Recommended use	Coating for professional use	
Responsible party	Pro Line Performance Products PO Box 1136 Olympia, WA 98507	
Telephone	Product information	www.LumabaseCoatings.com
	Medical emergency	800-535-5053
	Transportation emergency	800-535-5053

2. HAZARDS IDENTIFICATION

GHS-Classification

Flammable liquids, Category 2 ; Skin corrosion/irritation, Category 2 ; Serious eye damage/eye irritation, Category 2A ; Skin sensitisation, Category 1 ; Carcinogenicity, Category 1A ; Target Organ Systemic Toxicant - Single exposure, Category 3 ; Target Organ Systemic Toxicant - Repeated exposure, Category 2

GHS-Labeling

Hazard symbols:



Signal word: Danger

Hazard statements: Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause cancer. May cause damage to organs through prolonged or repeated exposure.

Precautionary statements: Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplemental first aid instructions on this label). If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local regulations.

Other hazards which do not result in classification

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

SAFETY DATA SHEET

40

Version: 1.0

US - en

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:
26.4 %

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of synthetic resins, pigments, and solvents

Components

CAS-No.	Chemical name	Concentration
100-41-4	Ethylbenzene	1.9%
108-10-1	Methyl isobutyl ketone	18.0%
111-76-2	Ethylene glycol monobutyl ether	3%
13048-33-4	1,6 hexanediol diacrylate	0.0 - 1.0%
1330-20-7	Xylene	7%
1333-86-4	Carbon black	0.1%
13463-67-7	Titanium dioxide	14.1%
14808-60-7	Quartz-crystalline silica	0.2%
25068-38-6	Epoxy resin	15 - 26%
3524-68-3	Methacrylic monomers	0.0 - 1.0%
4986-89-4	Pentaerythritol tetraacrylate	0.0 - 1.0%
67-63-0	Isopropyl alcohol	1 - 4%

Any concentration shown as a range is due to batch variation.
Non-regulated ingredients 20 - 30%
OSHA Hazardous: Yes

4. FIRST AID MEASURES

Eye contact: Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact: Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation: Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion: If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed

SAFETY DATA SHEET

40

Version: 1.0

US - en

Inhalation: May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion: May result in gastrointestinal distress.

Skin or eye contact: May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Indication of Immediate medical attention and special treatment needed if necessary: No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical

Extinguishing media which shall not be used for safety reasons: High volume water jet

Hazardous combustion products: CO, CO₂, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

Fire and Explosion Hazards: Flammable liquid. Vapor/air mixture will burn when an ignition source is present.

Special Protective Equipment and Fire Fighting Procedures: Full protective flameproof clothing should be worn as appropriate. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

6. ACCIDENTAL RELEASE MEASURES

Procedures for cleaning up spills or leaks: Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

Environmental precautions: Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

7. HANDLING AND STORAGE

Precautions for safe handling: Observe label precautions. Keep away from heat, sparks, flame, static discharge and other sources of ignition. VAPORS MAY CAUSE FLASH FIRE. Close container after each use. Ground containers when pouring. Do not transfer contents to bottles or unlabeled containers. Wash thoroughly after handling and before eating or smoking. Do not store above 49 °C (120 °F). If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

Advice on protection against fire and explosion: Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

SAFETY DATA SHEET

40

Version: 1.0

US - en

Storage

Requirements for storage areas and containers: Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage: Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

OSHA/NFPA Storage Classification: IB

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls and work practices: Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

National occupational exposure limits

CAS-No.	Chemical name	Source	Time	Type	Value	Note
108-10-1	Methyl isobutyl ketone	ACGIH	15 min	STEL	75 ppm	
		ACGIH	8 hr	TWA	20 ppm	
		OSHA	8 hr	TWA	100 ppm	
13463-67-7	Titanium dioxide	OSHA	8 hr	TWA	15 mg/m ³	Total Dust
1330-20-7	Xylene	ACGIH	15 min	STEL	150 ppm	
		ACGIH	8 hr	TWA	100 ppm	
		OSHA	8 hr	TWA	100 ppm	
111-76-2	Ethylene glycol monobutyl ether	OSHA	8 hr	TWA	50 ppm	Skin
100-41-4	Ethylbenzene	ACGIH	8 hr	TWA	20 ppm	
		OSHA	8 hr	TWA	100 ppm	
14808-60-7	Quartz-crystalline silica	OSHA	8 hr	TWA	0.3 mg/m ³	Total Dust
		OSHA	8 hr	TWA	50 ug/m ³	Respirable Dust
1333-86-4	Carbon black	ACGIH	8 hr	TWA	3 mg/m ³	
		OSHA	8 hr	TWA	3.5 mg/m ³	

Glossary

CEIL	Ceiling exposure limit
STEL	Short term exposure limit
TL	Threshold limits
TLV	Threshold Limit Value
TWA	Time weighted average
TWAE	Time-Weighted Average

Protective equipment: Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection: Do not breathe vapors or mists. Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C) and particulate filter (NIOSH TC-84A) during application and until all vapors and spray mists are exhausted. In confined spaces, or in situations where continuous spray operations are typical, or if proper air-purifying respirator fit is not possible, wear a positive pressure, supplied-air respirator (NIOSH TC-19C). In all cases, follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area.

Eye protection: Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

Skin and body protection: Neoprene gloves and coveralls are recommended.

Hygiene measures: Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or

SAFETY DATA SHEET

40

Version: 1.0

US - en

thinners.

Environmental exposure controls: Do not let product enter drains.

For ecological information, refer to Ecological Information Section 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form: liquid **Colour:** grey

Flash point	61 °F	
Lower Explosive Limit	1.2 %	
Upper Explosive Limit	8 %	
Evaporation rate	Slower than Ether	
Vapor pressure of principal solvent	6.0 hPa	
Water solubility	moderate	
Vapor density of principal solvent (Air = 1)	3.46	
Approx. Boiling Range	114 °C	
Approx. Freezing Range	-84 – 1843 °C	
Gallon Weight (lbs/gal)	10.98	
Specific Gravity	1.32	
Percent Volatile By Volume	52.56%	
Percent Volatile By Weight	33.40%	
Percent Solids By Volume	47.44%	
Percent Solids By Weight	66.60%	
pH (waterborne systems only)	Not applicable	
Partition coefficient: n-octanol/water	No data available	
Ignition temperature	224 °C	DIN 51794
Decomposition temperature	Not applicable.	
Viscosity (23 °C)	Not applicable.	ISO 2431-1993
VOC* less exempt (lbs/gal)	3.7	
VOC* as packaged (lbs/gal)	3.7	

* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

10. STABILITY AND REACTIVITY

Stability: Stable

Conditions to avoid: Stable under recommended storage and handling conditions (see section 7).

Materials to avoid: None reasonably foreseeable.

Hazardous decomposition products: When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

Hazardous Polymerization: Will not occur.

Sensitivity to Static Discharge: Solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

SAFETY DATA SHEET

40

Version: 1.0

US - en

Sensitivity to Mechanical Impact: None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion: May result in gastrointestinal distress.

Skin or eye contact: May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity

not hazardous

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

Not classified according to GHS criteria

% of unknown composition: 26.4 %

Skin corrosion/irritation

Methyl isobutyl ketone	Category 3
Epoxy resin	Category 2
Xylene	Category 2
Ethylene glycol monobutyl ether	Category 2
Ethylbenzene	Category 2
1,6 hexanediol diacrylate	Category 2
Methacrylic monomers	Category 2
Pentaerythritol tetraacrylate	Category 2

Serious eye damage/eye irritation

Methyl isobutyl ketone	Category 2A
Epoxy resin	Category 2A
Xylene	Category 2A
Ethylene glycol monobutyl ether	Category 2A
Isopropyl alcohol	Category 2A
1,6 hexanediol diacrylate	Category 2A
Methacrylic monomers	Category 2A
Pentaerythritol tetraacrylate	Category 2A

Respiratory sensitisation

Not classified according to GHS criteria

Skin sensitisation

Epoxy resin	Category 1
1,6 hexanediol diacrylate	Category 1

SAFETY DATA SHEET

40

Version: 1.0

US - en

Methacrylic monomers Category 1
Pentaerythritol tetraacrylate Category 1

Germ cell mutagenicity

Not classified according to GHS criteria

Carcinogenicity

Titanium dioxide Category 2
Ethylbenzene Category 2
Quartz-crystalline silica Category 1A
Carbon black Category 2

Toxicity for reproduction

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure

No data available.

Target Organ Systemic Toxicant - Repeated exposure

• Inhalation

Respiratory system Quartz-crystalline silica

Aspiration toxicity

Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.): No information available.

Symptoms related to the physical, chemical and toxicological characteristics:

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorption, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant. Low molecular epoxy constituents are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies. Avoid skin and eye contact. Avoid inhalation of vapour or mist.

Whether the hazardous chemical is listed by NTP, IARC or OSHA:

Methyl isobutyl ketone IARC 2B
Titanium dioxide IARC 2B
Ethylbenzene IARC 2B
Quartz-crystalline silica IARC 1
Carbon black IARC 2B

12. ECOLOGICAL INFORMATION

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

SAFETY DATA SHEET

40

Version: 1.0

US - en

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

14. TRANSPORT INFORMATION

International transport regulations

IMDG (Sea transport)

UN number: 1263
Proper shipping name: PAINT

Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: II
Marine Pollutant: no
EmS: F-E,S-E

ICAO/IATA (Air transport)

UN number: 1263
Proper shipping name: PAINT

Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: II

DOT

UN number: 1263
Proper shipping name: PAINT

Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: II
Marine Pollutant: no

The transport information is for bulk shipments. Exceptions may apply for smaller containers.

Matters needing attention for transportation: Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. REGULATORY INFORMATION

TSCA Status: In compliance with TSCA Inventory requirements for commercial purposes.

DSL Status: All components of the mixture are listed on the DSL.

Photochemical Reactivity: Photochemically reactive

SAFETY DATA SHEET

40

Version: 1.0

US - en

Regulatory information:

CAS #	Ingredient	EPCRA					CERCLA	CAA	
		302	TPQ	RQ	311/312	313	RQ(lbs)	HAP	
108-10-1	Methyl isobutyl ketone	N	NR	NR	A,C,F	Y	5,000	Y	
25068-38-6	Epoxy resin	N	NR	NR	C	N	NR	N	
13463-67-7	Titanium dioxide	N	NR	NR	A	N	NR	N	
1330-20-7	Xylene	N	NR	NR	A,C,F	Y	100	Y	
111-76-2	Ethylene glycol monobutyl ether	N	NR	NR	A,C,F	Y	NR	N	
100-41-4	Ethylbenzene	N	NR	NR	A,C,F	Y	1,000	Y	
67-63-0	Isopropyl alcohol	N	NR	NR	A,C,F,N,P,R	N	NR	N	
14808-60-7	Quartz-crystalline silica	N	NR	NR	A,C	N	NR	N	
1333-86-4	Carbon black	N	NR	NR	C	N	NR	N	
13048-33-4	1,6 hexanediol diacrylate	N	NR	NR	C	N	NR	N	
3524-68-3	Methacrylic monomers	N	NR	NR	NA	N	NR	N	
4986-89-4	Pentaerythritol tetraacrylate	N	NR	NR	NA	N	NR	N	

16. OTHER INFORMATION

HMIS rating: H: 2 ; F: 3 ; R: 1

Glossary of Terms

ACGIH	American Conference of Governmental Industrial Hygienists.
IARC	International Agency for Research on Cancer.
NTP	National Toxicology Program.
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration.
STEL	Short term exposure limit
TWA	Time-weighted average.
PNOR	Particles not otherwise regulated.
PNOC	Particles not otherwise classified.

EPCRA	Emergency Planning and Community Right-to-know Act (aka Title III, SARA)
302	Extremely hazardous substances
311/312 Categories	F = Fire Hazard R = Reactivity Hazard P = Pressure Related Hazard A = Acute Hazard C = Chronic Hazard
313 Information	Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372.
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980.
HAP	Listed as a Clean Air Act Hazardous Air Pollutant.
TPQ	Threshold Planning Quantity.
RQ	Reportable Quantity
NA	not available

SAFETY DATA SHEET

40

Version: 1.0

US - en

NR | not regulated

NOTE: The list (above) of glossary terms may be modified.

Information is accurate and subject to change as new information is received.

The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS Prepared by Regulatory Affairs

Report version

Version: 1.0

Changes:

Revision Date: 2019-03-05