

LV Matting Agent

Technical Data Sheet #LV4100



Components

LV4100 LV Matting Agent

Mix by Volume

- Product is designed to be mixed with Lumabase LV1000 and LV2000 Clear Coats as recommended below.
- Product can be mixed by weight at different levels to achieve the below desired levels of gloss.
 - Flat = 0–15 gloss level
 - Satin = 20–45 gloss level
 - Semi = 50–65 gloss level

Application

- LV4100 **must** be shaken thoroughly before each use.
 - **VOC**
Max VOC (LE) 250 g/l – 2.1 lbs/gal

Safety & Health

Read and follow all technical product information, labels, and SDS prior to application. Keep product out of reach of children and animals. Always wear proper safety equipment (respirator, gloves, eye, and clothing protection) when using this product.

Refer to all labels on products and information sheets for hazards and proper handling procedures for each component. Read the Safety Data Sheets (SDS) supplied with the materials.

KEEP OUT OF REACH OF CHILDREN

FLAT		PINT GRAMS		PINT GRAMS
	LV2000 LV Gloss Clear	143	LV1000 LV Panel Clear	138
	LV9075 LV Med Activator	94	LV9075 LV Med Activator	95
	LV4100 LV Matting Agent	264	LV4100 LV Matting Agent	267
SATIN				
	LV2000 LV Gloss Clear	157	LV1000 LV Panel Clear	152
	LV9075 LV Med Activator	94	LV9075 LV Med Activator	95
	LV4100 LV Matting Agent	248	LV4100 LV Matting Agent	253
SEMI				
	LV2000 Gloss Clear	174	LV1000 LV Panel Clear	169
	LV9075 LV Med Activator	94	LV9075 LV Med Activator	96
	LV4100 LV Matting Agent	230	LV4100 LV Matting Agent	234

Disposal

Dispose of all paint and paint related materials in accordance with state and provincial regulations.