

Basecoat Additive

Technical Data Sheet #L2200



Description

L2200 can be used as a colorless basecoat designed for tri-coats, mid-coats, wet beds, inner-coat clear, design work and light or hard to control metallics. This basecoat additive is not intended for use as a durable topcoat clear and must be overcoated with clearcoat.

Components

L2200 Basecoat Additive

Mix by Volume

WET BED – INTER COAT CLEAR

- 2 Parts L2200 Basecoat Additive
- 1 Part 7070, 8080, 9090 Reducer

TRANSLUCENT BLENDING PROCEDURE

- 1 Part pre-reduced paint with 7070, 8080, 9090 Reducer
- 1 Part pre-reduced L2200 with 7070, 8080, 9090 Reducer
- For difficult colors add 5% L100 Flop Adjuster to the translucent (transparent) blending step.

Pot Life

- N/A

Application

- Degrease then wet sand P800 – P1000 grit or dry sand P400 – P600 grit
- Re-clean surface after sanding
- Apply 1 to 2 single coats with 4-8 minute flash between coats
- Flash off for 15-20 minutes before applying clear

Disposal

Dispose of all paint and paint related materials in accordance with state and local regulations.

Safety & Health

Read and follow all technical product information, labels, and SDS prior to application. Keep product out of reach of children and animals. Always wear proper safety equipment (respirator, gloves, eye, and clothing protection) when using this product.

Refer to all labels on products and information sheets for hazards and proper handling procedures for each component. Read the Safety Data Sheets (SDS) supplied with the materials.

KEEP OUT OF REACH OF CHILDREN